

MODEL	Safe Load Rating (lbs)	Not to exceed Load (lbs)
2LOR2	6,000	8,000
2LOR3	6,000	8,000
2LOR4	6,000	8,000
2LOR6	6,000	8,000
2LOR8	6,000	8,000
2LOR10	6,000	8,000
2LOR12	6,000	8,000

3LOR2	9,000	12,000
3LOR3	9,000	12,000
3LOR4	9,000	12,000
3LOR6	9,000	12,000
3LOR8	9,000	12,000
3LOR10	9,000	12,000
3LOR12	9,000	12,000

4LOR2	12,000	16,000
4LOR3	12,000	16,000
4LOR4	12,000	16,000
4LOR6	12,000	16,000
4LOR8	12,000	16,000
4LOR10	12,000	16,000
4LOR12	12,000	16,000

6LOR2	18,000	24,000
6LOR3	18,000	24,000
6LOR4	18,000	24,000
6LOR6	18,000	24,000
6LOR8	18,000	24,000
6LOR10	18,000	24,000
6LOR12	18,000	24,000

8LOR2	24,000	32,000
8LOR3	24,000	32,000
8LOR4	24,000	32,000
8LOR6	24,000	32,000
8LOR8	24,000	32,000
8LOR10	24,000	32,000
8LOR12	24,000	32,000

10LOR2	30,000	40,000
10LOR3	30,000	40,000
10LOR4	30,000	40,000
10LOR6	30,000	40,000
10LOR8	30,000	40,000
10LOR10	30,000	40,000
10LOR12	30,000	40,000

12LOR2	36,000	48,000
12LOR3	36,000	48,000
12LOR4	36,000	48,000
12LOR6	36,000	48,000
12LOR8	36,000	48,000
12LOR10	36,000	48,000
12LOR12	36,000	48,000

14LOR2	42,000	56,000
14LOR3	42,000	56,000
14LOR4	42,000	56,000
14LOR6	42,000	56,000
14LOR8	42,000	56,000
14LOR12	42,000	56,000

MODEL	Safe Load Rating (lbs)	Not to exceed Load (lbs)
6LOV	25,000	30,000
8LOV	36,000	45,000
10LOV	47,000	60,000
12LOV	58,000	75,000
14LOV	60,000	85,000

LOR SELECTION TABLE

Pipe size	Beam size						
	2"	3"	4"	6"	8"	10"	12"
1	2LOR1	3LOR1	4LOR1	6LOR1	8LOR1	10LOR1	12LOR1
1.5	2LOR1	3LOR1	4LOR1	6LOR1	8LOR1	10LOR1	12LOR1
2	2LOR1.5	3LOR1.5	4LOR1.5	6LOR1.5	8LOR1.5	10LOR1.5	12LOR1.5
3	2LOR2	3LOR2	4LOR2	6LOR2	8LOR2	10LOR2	12LOR2
4	2LOR3	3LOR3	4LOR3	6LOR3	8LOR3	10LOR3	12LOR3
6	2LOR4	3LOR4	4LOR4	6LOR4	8LOR4	15LOR4	12LOR4
8	2LOR6	3LOR6	4LOR6	6LOR6	8LOR6	10LOR6	12LOR6
10	2LOR6	3LOR6	4LOR6	6LOR6	8LOR6	10LOR6	12LOR6
12	NA	NA	4LOR8	6LOR8	8LOR8	10LOR8	12LOR8
14	NA	NA	4LOR8	6LOR8	8LOR8	10LOR8	12LOR8
16	NA	NA	4LOR8	6LOR8	8LOR8	10LOR8	12LOR8
18	NA	NA	4LOR8	6LOR8	8LOR8	10LOR8	12LOR8
20	NA	NA	4LOR8	6LOR8	8LOR8	10LOR8	12LOR8
24	NA	NA	4LOR8	6LOR8	8LOR8	10LOR8	12LOR8
26	NA	NA	4LOR8	6LOR8	8LOR8	10LOR8	12LOR8
30	NA	NA	4LOR8	6LOR8	8LOR8	10LOR8	12LOR8
32	NA	NA	4LOR8	6LOR8	8LOR8	10LOR8	12LOR8
34	NA	NA	4LOR10	6LOR10	8LOR10	10LOR10	12LOR10
36	NA	NA	4LOR10	6LOR10	8LOR10	10LOR10	12LOR10
38	NA	NA	4LOR12	6LOR12	8LOR12	10LOR12	12LOR12
40	NA	NA	4LOR12	6LOR12	8LOR12	10LOR12	12LOR12
42	NA	NA	4LOR12	6LOR12	8LOR12	10LOR12	12LOR12

LOR selection example:

A 3" pipe is supported on a 6" wide beam.

Select the pipe size on the left.

Then select the beam size on the top.

The LOR size will be: 6LOR2.

Note: LOV's are for 12" pipe and above (price does not include the support carriages).